



05000C4 Motor Oil 5W-30 Premium Synthetic C4 Renault

Document version: 11 May 2024



Description

This premium synthetic fuel-saving 'LOW SAPS' (ACEA C4) motor oil has been specially developed for Renault cars and light commercial vehicles with petrol, LPG, and diesel engines, modern three-way catalysts and DPF filters for which an ACEA C4 oil is specified. This motor oil helps give a longer particulate filter life.

Application manual

According to the specifications of

ACEA C4
Fiat 9.55535-S4
MB-Approval 226.51
Renault RN 0720

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001C4	1 L	6	450
05005C4	5 L	4	112
05020C4	20 L	1	30
05B20C4	20 L	1	-
05060C4	60 L	1	12
05205C4	205 L	1	2
05999C4	1000 L	1	-
P05000C4	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.852	kg/l	ASTM D4052
Viscosity	5W-30		SAE J300
Kinematic Viscosity at 40°C	67.3	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	11.5	mm ² /s	ASTM D445
Viscosity Index	167		ASTM D2270
Dynamic Viscosity at -30°C	6300	mPa.s	ASTM D5293
Flashpoint COC	203	°C	ASTM D92
Pourpoint	-33	°C	ASTM D97
Total Base Number	7.2	mgKOH/g	ASTM D2896
Sulphated Ash	0.5	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.