



05000S Motor Oil 5W-50 Premium Synthetic SN

Document version: 11 May 2024



Description

This premium synthetic engine oil has been specially developed for the perfect lubrication of high performance and high powered petrol and diesel engines with or without a turbocharger. The formulation provides excellent protection against friction and ensures superior lubricating oil film at high speeds.

According to the specifications of

ACEA A3/B4
API CF / SN

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001S	1 L	6	450
05004S	4 L	4	112
05005S	5 L	4	112
05020S	20 L	1	30
05060S	60 L	1	6
05205S	205 L	1	2
05999S	1000 L	1	-
P05000S	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.852	kg/l	ASTM D4052
Viscosity SAE	5W-50		
Kinematic Viscosity at 40°C	118	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	18	mm ² /s	ASTM D445
Viscosity Index	170		ASTM D2270
Dynamic Viscosity at -30°C	6200	mPa.s	ASTM D5293
Flashpoint COC	235	°C	ASTM D92
Pourpoint	-30	°C	ASTM D6892
Total Base Number	9.6	mgKOH/g	ASTM D2896
Sulphated Ash	1.1	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.