



16000ZF6 ATF Automatic Transmission Fluid M-1375.4

Document version: 11 May 2024



Description

This premium synthetic automatic transmission oil has been specially developed for all 6 speed ZF transmissions and other applications for which manufacturers require an M-1375.4 specification.

According to the specifications of

Aston Martin ATF M-1375.4
BMW 83 22 0 142 516 / 83 22 2 305 396
Bentley PY112995PA
Hyundai 0400000C90SG
Jaguar ATF M-1375.4 / Fluid 8432
Land Rover TYK 500050
Maserati 231603 / Gran Turismo ATF M-1375.4 / Quattroporte ATF M-1375.4
Porsche ATF M-1375.4
Rolls Royce ATF M-1375.4
VW G 055 005

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 16001ZF6 | 1 L | 6 | 450 |
| 16004ZF6 | 4 L | 4 | 112 |
| 16020ZF6 | 20 L | 1 | 30 |
| 16060ZF6 | 60 L | 1 | 6 |
| 16205ZF6 | 205 L | 1 | 2 |
| 16999ZF6 | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|-------------------------------|-------|--------------------|--------|
| Density at 15°C | 0.845 | kg/l | |
| Colour | brown | | |
| Viscosity | 10W | | |
| Kinematic Viscosity at 40°C | 26.8 | mm ² /s | |
| Kinematic Viscosity at 100°C | 5.6 | mm ² /s | |
| Viscosity Index | 151 | | |
| Flashpoint COC | 210 | °C | |
| Pourpoint | -51 | °C | |
| Brookfield Viscosity at -40°C | 8500 | mPa.s | |

These characteristics are typical of current production. Variations in these characteristics may occur.