



# 18000TR Gear Oil 75W-140 Premium Synthetic Truck

Document version: 11 May 2024



## Description

This premium synthetic SAE 75W-140 transmission oil is an Extreme Pressure (EP) transmission oil for application in very heavy duty rear axles, end drives of commercial vehicles and industrial equipment for which manufacturers specify a SAE 75W-140 GL-5 oil.

## According to the specifications of

API GL-4 / GL-5 / MT-1  
Ford M2C192-A  
MAN 3343 Type S / 341 Type E3  
MB 235.8  
MIL-PRF 2105E  
Mack GO-J  
SAE J 2360  
Scania STO 1:0  
ZF TE-ML 02B / 05B / 12B / 16F

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
18020TR	20 L	1	30
18060TR	60 L	1	6
18205TR	205 L	1	2
18999TR	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.873	kg/l	D 4052
Viscosity	75W-140		
Kinematic Viscosity at 40°C	186	mm <sup>2</sup> /s	D 445
Kinematic Viscosity at 100°C	24.9	mm <sup>2</sup> /s	D 445
Viscosity Index	166		D 2270
Flashpoint COC	174	°C	D 92
Pourpoint	-42	°C	D 97
Brookfield Viscosity at -40°C	145000	mPa.s	D 2983

These characteristics are typical of current production. Variations in these characteristics may occur.