



## 88000A Antifreeze MPG

Document version: 11 May 2024



### Description

This MPM silicate-free MPG (Monopropylene glycol) antifreeze provides excellent protection of aluminium and metal alloy components within cooling systems. The non-toxic, environmentally friendly multipurpose product can also be used in boats and recreation vehicles (RVs) to protect inboard engines, drinking water and toilet systems against freezing. This Antifreeze MPG is environmentally friendly, and can be safely disposed of and is also suitable for food industry applications where applicable. This antifreeze should be diluted before use, as per manufacturer's specification.

### According to the specifications of

VW TL 52 176

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
88005A	5 L	4	112
88020A	20 L	1	30
88060A	60 L	1	6
88205A	205 L	1	2
88999A	1000 L	1	-

### Standard analyses

TEST	VALUE	METHOD
Density at 20°C	1.042	kg/l
Colour	fluorescent orange / red	
Freezing point at $\frac{1}{3}$ antifreeze + $\frac{2}{3}$ water	-16	°C
Freezing point at 1 antifreeze + 1 water	-36	°C
Boiling Point	165	°C
Water	4	mass%
Copper Corrosion Test-reserve Alkanity	6.3	

These characteristics are typical of current production. Variations in these characteristics may occur.