



# 05000DPF Motor Oil 5W-30 Premium Synthetic C3 DPF

Document version: Apr 22, 2024



## Description

This premium synthetic motor oil has been specially developed for BMW and Mercedes-Benz engines. This motor oil has the approvals of BMW Long Life 04 and Mercedes-Benz Long Life 229.51 / 229.52.. This SAE 5W-30 motor oil with ACEA C3 standard is recommended for petrol and diesel engines fitted with exhaust gas after-treatment systems.

## Application manual

## According to the specifications of

ACEA C3  
API SN Plus / SP  
BMW LL-04  
Chrysler MS 11106  
Fiat 9.55535-S3  
GM dexos 2  
MB-Approval 229.51 / 229.52  
Opel OV 040 1547 - D30 / OV 040 1547 - G30  
Renault RN 0700 / RN 0710  
VW 502.00 / 505.00 / 505.01

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DPF	1 L	6	450
05005DPF	5 L	4	112
05020DPF	20 L	1	-
05B20DPF	20 L	1	-
05060DPF	60 L	1	-
05205DPF	205 L	1	2
05999DPF	1000 L	1	-
P05000DPF	1 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.850	kg/l	ASTM D4052
Viscosity	5W-30		SAE
Kinematic Viscosity at 40°C	67.1	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	12.2	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	182		ASTM D2270
Dynamic Viscosity at -30°C	5400	mPa.s	ASTM D5293
Flashpoint COC	234	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	8.0	mgKOH/g	ASTM D2896
Sulphated Ash	0.77	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.