



18000G Gearbox Oil 75W-90 GL-3/4/5 Premium Synthetic TDL

Document version: 27 Apr 2024



Description

This premium synthetic SAE 75W-90 TDL transmission oil is a universal synthetic transmission oil for the total drive line and has been specially developed for many types of transmissions, end drives and transfer box in cars and heavy duty commercial vehicles.

According to the specifications of

API GL-3 / GL-4 / GL-5 / MT-1
Arvin Meritor 0-76-N
DAF GL-5 MIL-PRF-2105E
IVECO MIL-PRF-2105E
MAN 341 Type E3 / 341 Type Z2 / 342 Type M3
MB 235.8
Mack GO-J
Renault B0032/3 Annex 3
SAE J 2360
Scania STO 1:0
VW G 052 145 / 052 911
Volvo 97312
ZF TE-ML 05B / 07A / 08 / 12B / 12L / 12N / 16F / 17B / 19C / 21B

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 18001G | 1 L | 6 | 450 |
| 18004G | 4 L | 4 | 112 |
| 18020G | 20 L | 1 | 30 |
| 18060G | 60 L | 1 | 6 |
| 18205G | 205 L | 1 | 2 |
| 18999G | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|-------------------------------|--------|--------------------|
| Density at 15°C | 0.868 | kg/l |
| Viscosity | 75W-90 | |
| Kinematic Viscosity at 40°C | 78.1 | mm ² /s |
| Kinematic Viscosity at 100°C | 15.2 | mm ² /s |
| Viscosity Index | 207 | |
| Flashpoint COC | 165 | °C |
| Pourpoint | -48 | °C |
| Brookfield Viscosity at -40°C | 90000 | mPa.s |

These characteristics are typical of current production. Variations in these characteristics may occur.