



AD26000 Radiator Stop Leak and Conditioner

Document version: Apr 27, 2024



Description

MPM Radiator Stop Leak and Conditioner is used to prevent and repairs leakages in the radiator, water pump and cylinder head.

Main benefits

- Permanently and reliably seals/prevents hair line cracks and leakages.
- Lubricates the water pump.
- Eliminates the need of costly repairs.
- Protects the entire cooling system against rust and corrosion.
- Does not harm rubber hoses, plastics or metals such as copper and aluminium parts/gaskets.
- Is not poisonous and does not contain acids.

Application

Suitable for all petrol, diesel and LPG engine cooling systems with radiators made of aluminium, plastic or steel.

Mixable with water, cooling fluids and conventional anti-freeze.

Application manual

Shake well before use. Pour contents of 250 ml bottle into the cooling system of a warm engine (not hot) with the cabin heating switched 'on'. Keep the engine running for approximately 10 minutes or drive a short distance. The contents of one 250ml bottle is suitable to treat a cooling system holding up to 12 litres of coolant, antifreeze or water. Attention: Be careful whilst opening the radiator / cooling system hot coolant or steam may escape from the system.

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
AD26250	0.25 L	6	-

Standard analyses

TEST	VALUE	METHOD
Shelf life	1	year(s)
Density at 20°C	1.02	kg/l
Colour	brown	
pH	6	
Odour	neutral	

These characteristics are typical of current production. Variations in these characteristics may occur.