

BL021000 Marine FC-W Engine Oil 4-Stroke Outboard EHP 10W-40

Document version: 27 Apr 2024



Description

According to the specifications of

Packaging units

Standard analyses

This marine FC-W engine oil 4-Stroke outboard EHP has good wear protection under severe conditions and is designed for use in modern 4-stroke water-cooled inboard- and outboard engines. This engine oil meets the latest requirements set by the NMMA. Particularly suitable for use in engines of Mercruiser, Mercury, Suzuki, Honda, Yamaha, Nissan, Johnson/Evinrude, Chrysler Marine etc.

API SL NMMA FC-W (Certificate number: FB-44404M)

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL021001 BL021005	1 L 5 L	6 4	450 112
BL021020	20 L	1	30
BL021060	60 L	1	6
BL021205	205 L	1	2
BL021999	1000 L	1	<u>-</u>
PBL021000	1 L	1	=

TEST	VALUE		METHOD
Density at 15°C Viscosity	0.88 10W-40	kg/l	
SAE	10W-40		
Kinematic Viscosity at 100°C	14.3	mm2/s	
Viscosity Index	156		
Dynamic Viscosity at -25°C	6300	mPa.s	
Flashpoint COC	216	°C	
Pourpoint	-30	°C	
Total Base Number	7.7	mgKOH/g	

These characteristics are typical of current production. Variations in these characteristics may occur.