



BL032000 Marine Engine Oil Multi Grade 15W-40

Document version: 27 Apr 2024



Description

This universal mineral marine engine oil is specially suitable for use in the first generation normal duty petrol engines and diesel engines with or without turbocharged.

According to the specifications of

API CG-4
Allison C4
Caterpillar TO-2
Cummins
DAF
Deutz/MWM
Lister
MAN M 271
MB-Approval 228.1
Vetus
Volvo VDS
Yanmar

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL032001	1 L	6	450
BL032005	5 L	4	112
BL032020	20 L	1	30
BL032060	60 L	1	6
BL032205	205 L	1	2
BL032999	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.883	kg/l	
Viscosity	15W-40		
SAE	15W-40		
Kinematic Viscosity at 40°C	107	mm ² /s	
Kinematic Viscosity at 100°C	14	mm ² /s	
Viscosity Index	132		
Flashpoint COC	228	°C	
Pourpoint	-30	°C	
Total Base Number	6.1	mgKOH/g	
Sulphated Ash	1	mass%	

These characteristics are typical of current production. Variations in these characteristics may occur.