



## 20000LV Brake Fluid Low Viscosity DOT 4+ LV

Document version: 27 Apr 2024



### Description

This synthetic DOT 4+ Low Viscosity brake fluid has been specially developed for use in all hydraulically operated brake systems for which constructors specify a brake fluid of the type DOT 4+ Low Viscosity. This brake fluid is extremely suitable for brake systems with ESP and ABS systems.

### Application manual

According to the specifications of

BMW QV 34 1  
FMVSS 116 DOT 4  
GMW 3356  
ISO 4925 (CLASS 6)  
MB 331.0  
SAE J 1704  
VW 501.14

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
20250LV	0.25 L	12	-
20500LV	0.5 L	12	-
20001LV	1 L	6	450
20005LV	5 L	4	112
20020LV	20 L	1	30
20060LV	60 L	1	12
20205LV	205 L	1	2
20999LV	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 20°C	1.06	kg/l	
Colour	Yellow		
pH	7.5		
Kinematic Viscosity at 100°C	2.1	mm <sup>2</sup> /s	
Kinematic Viscosity at -40°C	650	mm <sup>2</sup> /s	
Wet Boiling Point	178	°C	
Boiling Point	272	°C	

These characteristics are typical of current production. Variations in these characteristics may occur.