



# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878  
Revision date: 3-3-2016 Supersedes: 29-9-2014 version: 4.5

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : MPM Industrial Gear Oil 320  
Product code : 39000F  
Product group : Blend

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use, Consumer use  
Industrial/Professional use spec : Non-dispersive use  
Used in closed systems  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

MPM International Oil Company  
Cyclotronweg 1  
2629 HN Delft - Nederland  
T +31 (0)15 2514030  
[pvhoorn@mpmoil.com](mailto:pvhoorn@mpmoil.com) - [www.mpmoil.com](http://www.mpmoil.com)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Not classified

##### Adverse physicochemical, human health and environmental effects

No additional information available.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains: Long chain alkyl amine. May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Alkyl phosphate	CAS-No.: 190454-07-0 EC-No.: 696-070-0	$\geq 0,1 - \leq 0,24$	Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Long chain alkyl amine	CAS-No.: 68955-53-3 EC-No.: 273-279-1 REACH-no: 01-2119456798-18	$\geq 0,1 - \leq 0,2$	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 (M=0)

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General	: In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).
After inhalation	: No special measures are necessary.
After skin contact	: Wash with plenty of soap and water.
After eye contact	: Wash immediately with lots of water.
After ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Powder, alcohol-resistant foam, water spray, carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available.

# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 5.3. Advice for firefighters

- Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.  
Other information : Use water spray/stream to protect personnel and to cool endangered containers. Exercise caution when fighting any chemical fire.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable protective clothing and eye/face protection.

#### 6.1.2. For emergency responders

- Protective equipment : Wear respiratory protection. Wear suitable protective clothing and gloves.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Prevent spreading over great surfaces (e.g. by damming or installing oil booms).  
Methods for cleaning up : Clean up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).  
Other information : Can be slippery on hard, smooth walking area.

### 6.4. Reference to other sections

Information on disposal - see Section 13. Information on personal protective equipment - see Chapter 8. Information on safe handling - see Section 7.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.  
Handling temperature : < 40 °C  
Hygiene measures : When using do not eat, drink or smoke. Wash hands before breaks and at the end of work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Provide for sufficient ventilation and punctiform suction at critical points.  
Storage conditions : Store in original container.  
Incompatible products : Do not use with strong oxidizing agents, nor with strong acids or strong bases.  
Storage temperature : < 40 °C  
Storage area : Ensure adequate ventilation of the storage area. Keep container tightly closed and dry.

### 7.3. Specific end use(s)

No additional information available.

# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1. National occupational exposure and biological limit values

MPM Industrial Gear Oil 320	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOELV TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>

##### 8.1.2. Recommended monitoring procedures

No additional information available.

##### 8.1.3. Air contaminants formed

No additional information available.

##### 8.1.4. DNEL and PNEC

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m<sup>3</sup> oilspray (TWA, 8 hour workday) is recommended.

##### 8.1.5. Control banding

No additional information available.

#### 8.2. Exposure controls

##### 8.2.1. Appropriate engineering controls

###### Technical measures:

If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.

##### 8.2.2. Personal protection equipment

###### Personal protective equipment:

Gloves. Safety glasses.

###### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

###### Eye protection:

Safety glasses

##### 8.2.2.2. Skin protection

###### Skin and body protection:

None under normal use

###### Hand protection:

Wear suitable gloves.

###### Other skin protection

###### Materials for protective clothing:

Type of chemical protective gloves to choose depends on the concentration and quantity of dangerous substances as well as on work place specifications. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Suitable material: nitrile rubber. PVC (Polyvinyl chloride).

##### 8.2.2.3. Respiratory protection

###### Respiratory protection:

Not necessary with sufficient ventilation

##### 8.2.2.4. Thermal hazards

No additional information available.

# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.2.3. Environmental exposure controls

No additional information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily.
Colour	: Amber.
Odour	: characteristic.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: -21 °C
Boiling point	: No data available.
Flash point	: > 240 °C ASTM D92
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: No data available.
Vapour pressure	: No data available.
Relative vapour density at 20°C	: No data available.
Relative density	: No data available.
Density	: 900 kg/m <sup>3</sup> 15C
Solubility	: Water: practically insoluble
Log Pow	: No data available.
Viscosity, kinematic	: 320 mm <sup>2</sup> /s 40C
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

### 9.2. Other information

No additional information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal use.

### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

### 10.3. Possibility of hazardous reactions

No additional information available.

### 10.4. Conditions to avoid

None under normal use.

### 10.5. Incompatible materials

Oxidizing substances. Acids and bases.

### 10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

Long chain alkyl amine (68955-53-3)	
LD50 oral rat	612 mg/kg
LD50 dermal rat	251 mg/kg
LC50 Inhalation - Rat [ppm]	157 ppm/4h
ATE CLP (oral)	612 mg/kg bodyweight
ATE CLP (dermal)	251 mg/kg bodyweight
ATE CLP (gases)	157 ppmv/4h
ATE CLP (vapours)	0,5 mg/l/4h
ATE CLP (dust,mist)	0,05 mg/l/4h

Skin corrosion/irritation : Not classified  
Additional information : May cause an allergic skin reaction.  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified

Long chain alkyl amine (68955-53-3)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified

Long chain alkyl amine (68955-53-3)	
LOAEL (dermal, rat/rabbit, 90 days)	60 mg/kg bodyweight OECD 410
NOAEL (dermal, rat/rabbit, 90 days)	20 mg/kg bodyweight OECD 410
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

MPM Industrial Gear Oil 320	
Viscosity, kinematic	320 mm <sup>2</sup> /s 40C

### SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Long chain alkyl amine (68955-53-3)	
LC50 fish 1	1,3 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	0,24 – 6 mg/l Daphnia magna
EC50 72h - Algae [1]	0,44 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	0,078 mg/l Oncorhynchus mykiss @ 96d

# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.2. Persistence and degradability

#### MPM Industrial Gear Oil 320

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

### 12.3. Bioaccumulative potential

No additional information available.

### 12.4. Mobility in soil

No additional information available.

### 12.5. Results of PBT and vPvB assessment

No additional information available.

### 12.6. Other adverse effects

No additional information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Waste disposal according to official state regulations.
European List of Waste (LoW) code	: 13 02 00 - Waste engine, gear and lubricating oils. 13 02 05- Mineral-based non-chlorinated engine, gear and lubricating oils. 15 01 10 Packaging containing residues of or contaminated by dangerous substances.

## SECTION 14: Transport information

In accordance with ADR / IMDG

### 14.1. UN number

UN-No.	: Not applicable
UN-No. (IMDG)	: Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable

### 14.3. Transport hazard class(es)

**ADR**

Transport hazard class(es) (ADR)	: Not applicable
----------------------------------	------------------

**IMDG**

Transport hazard class(es) (IMDG)	: Not applicable
-----------------------------------	------------------

### 14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 14.6. Special precautions for user

#### Overland transport

No data available.

#### Transport by sea

No data available.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### 15.1.2. National regulations

No additional information available.

### 15.2. Chemical safety assessment

No additional information available.

## SECTION 16: Other information

### Full text of H- and EUH-statements

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH208	Contains: Long chain alkyl amine. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.



# MPM Industrial Gear Oil 320

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements	
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.