



02000 Motor Oil 15W-40 Turbo Universal

Document version: 27 Apr 2024



Description

This universal mineral motor oil has been specially developed for normal duty petrol engines and diesel engines of cars. This motor oil is also suitable for turbo diesel engines.

Application manual

According to the specifications of

ACEA A3/B4 / E2
API CG-4 / SL
Allison C4
Caterpillar TO-2
MAN M 271
MB 228.1
Volvo VDS

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
02001	1 L	6	450
02004	4 L	4	112
02005	5 L	4	112
02020	20 L	1	30
02060	60 L	1	6
02205	205 L	1	2
02999	1000 L	1	-
P02000	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.873	kg/l
Viscosity	15W-40	
Kinematic Viscosity at 40°C	90.5	mm ² /s
Kinematic Viscosity at 100°C	13.5	mm ² /s
Viscosity Index	151	
Flashpoint COC	200	°C
Pourpoint	-30	°C
Total Base Number	8.4	mgKOH/g
Sulphated Ash	1	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.