



# 05000S Motor Oil 5W-50 Premium Synthetic SN

Document version: Apr 22, 2024



## Description

This premium synthetic engine oil has been specially developed for the perfect lubrication of high performance and high powered petrol and diesel engines with or without a turbocharger. The formulation provides excellent protection against friction and ensures superior lubricating oil film at high speeds.

## According to the specifications of

ACEA A3/B4  
API CF / SN

## Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 05001S   | 1 L    | 6              | 450              |
| 05004S   | 4 L    | 4              | 112              |
| 05005S   | 5 L    | 4              | 112              |
| 05020S   | 20 L   | 1              | 30               |
| 05060S   | 60 L   | 1              | 6                |
| 05205S   | 205 L  | 1              | 2                |
| 05999S   | 1000 L | 1              | -                |
| P05000S  | 1 L    | 1              | -                |

## Standard analyses

| TEST                         | VALUE |                    | METHOD     |
|------------------------------|-------|--------------------|------------|
| Density at 15°C              | 0.852 | kg/l               | ASTM D4052 |
| Viscosity SAE                | 5W-50 |                    |            |
| Kinematic Viscosity at 40°C  | 118   | mm <sup>2</sup> /s | ASTM D445  |
| Kinematic Viscosity at 100°C | 18    | mm <sup>2</sup> /s | ASTM D445  |
| Viscosity Index              | 170   |                    | ASTM D2270 |
| Dynamic Viscosity at -30°C   | 6200  | mPa.s              | ASTM D5293 |
| Flashpoint COC               | 235   | °C                 | ASTM D92   |
| Pourpoint                    | -30   | °C                 | ASTM D6892 |
| Total Base Number            | 9.6   | mgKOH/g            | ASTM D2896 |
| Sulphated Ash                | 1.1   | mass%              | ASTM D874  |

These characteristics are typical of current production. Variations in these characteristics may occur.