



05000ESP-X Motor Oil 5W-30 Premium Synthetic ESP-X

Document version: 27 Apr 2024



Description

This premium synthetic ESP-X SAE 5W-30 fuel-saving engine oil has been specially formulated to meet the latest gasoline and diesel engine requirements for passenger cars, vans and SUVs.

Developed for better low speed pre-ignition protection, maintenance of exhaust after-treatment systems, optimal wear protection and improved fuel economy. This fully synthetic motor oil offers total engine protection and keeps the engine clean even in the toughest conditions.

Application manual

According to the specifications of

ACEA C2 / C3
API SN Plus / SP
BMW LL-04
Fiat 9.55535-S3
MB-Approval 229.51 / 229.52
Opel OV 040 1547 - D30 G30
Porsche C30
VW 504.00 / 507.00

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001ESP-X	1 L	6	450
05005ESP-X	5 L	4	112
05020ESP-X	20 L	1	30
05B20ESP-X	20 L	1	-
05060ESP-X	60 L	1	12
05205ESP-X	205 L	1	2
05999ESP-X	1000 L	1	-
P05000ESP-X	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density	0.850	kg/l	ASTM 4052
SAE	5W-30		
Kinematic Viscosity at 40°C	67	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	11.9	mm ² /s	ASTM D445
Viscosity Index	176		ASTM D2270
Dynamic Viscosity at -30°C	5980	mPa.s	ASTM D5293
Flashpoint	235	°C	ASTM D92
Pourpoint	-42	°C	ASTM D7346
Total Base Number	6.2	mgKOH/g	ASTM D2986
Sulphated Ash	0.75	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.