



# 16000FM ATF Automatic Transmission Fluid FM+

Document version: 27 Apr 2024



## Description

This premium synthetic automatic transmission oil with added friction modifier has been specially developed for all Audi, VW, BMW, Jaguar and Porsche models (amongst other things) with a Tiptronic automatic transmission.

## According to the specifications of

BMW LT 71141  
Citroën ATF LT 71141  
Fiat 9.55550-AG2  
Jaguar ATF LT 71141  
Land Rover ATF N 402  
MB 236.11  
PSA P/N Z000169752  
Peugeot ATF LT 71141  
Porsche ATF LT 71141  
VW G 052 162  
VW LT 71141  
VW TL 52 162

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001FM	1 L	6	450
16004FM	4 L	4	112
16020FM	20 L	1	30
16060FM	60 L	1	6
16205FM	205 L	1	2
16999FM	1000 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.849	kg/l
Colour	clear yellow / brown	
Viscosity	10W	
Kinematic Viscosity at 40°C	36.6	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	7.2	mm <sup>2</sup> /s
Viscosity Index	165	
Flashpoint COC	212	°C
Pourpoint	-48	°C
Total Base Number	2.7	mgKOH/g
Brookfield Viscosity at -40°C	12000	mPa.s

These characteristics are typical of current production. Variations in these characteristics may occur.