



Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 13-8-2014 Revision date: 11-12-2020 Supersedes: 12-11-2019 version: 2.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Complete Petrol System Treatment
UFI : 8H3K-U579-700S-AM95
Product code : AD01000
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Consumer use, Professional use
Function or use category : Fuel additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
Cyclotronweg 1
2629 HN Delft Delft - Nederland
T +31 (0)15 2514030 - F +31 (0)15 2514031
msds@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

CLP Signal word : Danger.
Hazardous ingredients : Solvent Naphta (Petroleum), Heavy Aromatic
Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways.
H412 - Harmful to aquatic life with long lasting effects.

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor.
P331 - Do NOT induce vomiting.
P405 - Store locked up.
P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics.	(CAS-No.) 1174522-09-8 (EC-No.) 918-481-9 (REACH-no) 01-2119457273-39	80 – 100	Asp. Tox. 1, H304
Solvent Naphta (Petroleum), Heavy Aromatic	(CAS-No.) 64742-94-5 (EC-No.) 265-198-5 (EC Index-No.) 649-424-00-3 (REACH-no) 01-2119463588-24	9 – 10	Carc. 2, H351 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Polyolefin alkylfenol alkylamine	(CAS-No.) 64742-94-5 (EC-No.) 265-198-5 (REACH-no) Polymer Reg.nr.: Conf0621	1,5 – 2,5	Skin Irrit. 2, H315
2-Ethylhexanol	(CAS-No.) 104-76-7 (EC-No.) 203-234-3 (REACH-no) 01-2119487289-20	0,6 – 0,9	Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
naphthalene	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2	0,4 – 0,7	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Diethylbenzeen	(CAS-No.) 25340-17-4 (EC-No.) EINECS:246-874-9	0,4 – 0,7	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General

: First aider: Pay attention to self-protection!. Remove to fresh air and keep at rest in a position comfortable for breathing. Symptoms of poisoning may develop several hours following exposure. Victim should be under medical observation for at least 48 hours after exposure.

After inhalation

: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or a doctor if you feel unwell. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

After skin contact

: Take off immediately all contaminated clothing. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Do not use solvents or thinners.

After eye contact

: If eye irritation persists: Get medical advice/attention. In case of eye contact, immediately rinse with clean water for 10-15 minutes.

After ingestion

: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

After inhalation

: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness.

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

After skin contact	: May be harmful in contact with skin. Repeated exposure may cause skin dryness or cracking.
After eye contact	: Causes serious eye irritation.
After ingestion	: Aspiration hazard. May be harmful if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Entering the lungs by ingestion or vomiting may cause severe lung damage. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Symptoms of respiratory complications (lung oedema) may occur several hours after.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: powder, alcohol-resistant foam, water spray, carbon dioxide.
Unsuitable extinguishing media	: High power water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: On heating/burning: release of (highly) toxic gases/vapours e.g.: carbon monoxide - carbon dioxide. In use, may form flammable/explosive vapour-air mixture.
-------------	--

5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Cool containers / tanks with spray water if possible.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Do not breathe gas/fumes/vapour/spray. Ensure adequate ventilation.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Wear respiratory protection.
----------------------	--------------------------------

6.2. Environmental precautions

Make sure spills can be contained (e.g. sump pallets or kerbed areas). Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb spillage to prevent material damage. Collect spillage.

6.4. Reference to other sections

Information on personal protective equipment - see Chapter 8. Information on disposal - see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: This product is not to be used under conditions of poor ventilation. Avoid aerosol formation. Take precautionary measures against static discharge.
Precautions for safe handling	: Obtain special instructions before use. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Ensure adequate air ventilation.
Hygiene measures	: Avoid all unnecessary exposure. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Store in a well-ventilated place. Keep container tightly closed. Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep container tightly closed. Store in a dry place. Store in a well-ventilated place. Keep cool.
Heat and ignition sources	: Protect from heat and direct sunlight.
Information on mixed storage	: May react violently with oxidants.
Storage area	: Store according to local legislation.
Special rules on packaging	: Keep only in original container.

7.3. Specific end use(s)

No additional information available

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Solvent Naphta (Petroleum), Heavy Aromatic (64742-94-5)

EU	IOELV TWA (mg/m ³)	500 mg/m ³
Germany	TRGS 910 Acceptable concentration notes	

naphthalene (91-20-3)

EU	Local name	Naphthalene
EU	IOELV TWA (mg/m ³)	50 mg/m ³ 29-05-1991
EU	IOELV TWA (ppm)	10 ppm 29-05-1991
EU	Notes	(Year of adoption 2010)
EU	Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations
Germany	TRGS 910 Acceptable concentration notes	
Ireland	Local name	Naphthalene
Ireland	OEL (8 hours ref) (mg/m ³)	50 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	10 ppm
Ireland	Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom	WEL TWA (mg/m ³)	50 mg/m ³

2-Ethylhexanol (104-76-7)

EU	Local name	2-ethylhexan-1-ol
EU	IOELV TWA (mg/m ³)	5,4 mg/m ³
EU	IOELV TWA (ppm)	1 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Germany	TRGS 910 Acceptable concentration notes	
Ireland	Local name	2-Ethylhexan-1-ol
Ireland	OEL (8 hours ref) (mg/m ³)	5,4 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	1 ppm
Ireland	Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom	Local name	2-ethylhexan-1-ol
United Kingdom	WEL TWA (mg/m ³)	5,4 mg/m ³
United Kingdom	WEL TWA (ppm)	1 ppm
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Additional information : Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40) 1200mg/m³

8.2. Exposure controls

Technical measures:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Gloves.

Materials for protective clothing:

Wear suitable protective clothing, gloves and eye/face protection

Hand protection:

Wear suitable gloves resistant to chemical penetration

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35		

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing, gloves and eye/face protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



Other information:

Wear suitable gloves.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 160 °C
Flash point	: ≈ 62 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 1 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 800 kg/m ³
Solubility	: Water: practically insoluble
Log Pow	: No data available
Viscosity, kinematic	: < 7 mm ² /s @ 100°C
Viscosity, dynamic	: No data available
Explosive properties	: Flammable or explosive vapour/air mixtures may be formed. Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: 0,6 – 7 vol %

9.2. Other information

VOC content : 5,38 % EU, 1993/13/EC; USA EPA Method 24/24A

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with oxidizing substances.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No naked flames, sparks, and do not smoke.

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.5. Incompatible materials

Strong oxidizing agent.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics. (1174522-09-8)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 4951 mg/m ³ @ 4h

Solvent Naphta (Petroleum), Heavy Aromatic (64742-94-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:EPA Fed Reg Vol 50, No. 188 1985 and as amended in Fed Reg Vol 52, No. 97, 1987
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 5 mg/l/4h

naphthalene (91-20-3)

LD50 oral rat	> 490 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 100 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	> 110 mg/l/4h

2-Ethylhexanol (104-76-7)

LD50 oral rat	2049 mg/kg
LD50 dermal rabbit	1970 mg/kg
LC50 Inhalation - Rat	2,5 mg/l/4h

Skin corrosion/irritation	: Frequent or prolonged contacts may defat and dry the skin, leading to discomfort and dermatitis
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Ethylhexanol (104-76-7)

NOAEL (chronic, oral, animal/male, 2 years)	750 mg/kg bodyweight
---	----------------------

Reproductive toxicity	: Not classified
-----------------------	------------------

Solvent Naphta (Petroleum), Heavy Aromatic (64742-94-5)

NOAEL (animal/male, F0/P)	35 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test
NOAEL (animal/female, F0/P)	125 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

naphthalene (91-20-3)	
LOAEL (animal/female, F0/P)	50 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
LOAEL (animal/female, F1)	450 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
NOAEL (animal/female, F0/P)	120 mg/kg bodyweight Animal: rabbit, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Solvent Naphta (Petroleum), Heavy Aromatic (64742-94-5)	
LOAEC (inhalation, rat, vapour, 90 days)	4,71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	2,355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)

naphthalene (91-20-3)	
LOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
LOAEC (inhalation, rat, vapour, 90 days)	0,011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

2-Ethylhexanol (104-76-7)	
NOAEC (inhalation, rat, gas, 90 days)	120 ppm OECD Guideline 413

Aspiration hazard : May be fatal if swallowed and enters airways.

Complete Petrol System Treatment	
Viscosity, kinematic	< 7 mm ² /s @ 100°C

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics. (1174522-09-8)	
LC50 fish 1	> 100 mg/l @96h Oncorhynchus mykiss
EC50 Daphnia 1	> 100 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	> 100 mg/l @72h Pseudokirchneriella subcapitata

Solvent Naphta (Petroleum), Heavy Aromatic (64742-94-5)	
LC50 fish 1	1 – 10 mg/l @96h
LC50 fish 2	0,58 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 other aquatic organisms 1	1 – 10 mg/kg @72h algae
EC50 Daphnia 1	1 – 10 mg/l @48h
EC50 Daphnia 2	0,76 mg/l Test organisms (species): Daphnia magna

naphthalene (91-20-3)	
LC50 fish 1	1,99 mg/l @96h Pimephales promelas

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LC50 fish 2	0,5 mg/l Fish
LC50 other aquatic organisms 1	2,96 mg/l @4h Selenastrum capricornutum
EC50 Daphnia 1	2,19 mg/l @48h Daphnia magna
NOEC (chronic)	0,59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
NOEC chronic fish	≈ 0,37 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'

2-Ethylhexanol (104-76-7)

LC50 fish 1	17,1 mg/l @96h Leuciscus idus
LC50 fish 2	17,1 mg/l leuciscus idus melanotus
EC50 Daphnia 1	39 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	11,5 mg/l @72h Algae Scenedesmus subspicatus
EC50 72h algae (1)	28,2 mg/l pimephales promelas
EC50 72h algae (2)	16,6 mg/l Desmodesmus subspicatus

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics. (1174522-09-8)

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

Solvent Naphta (Petroleum), Heavy Aromatic (64742-94-5)

Persistence and degradability	Poorly biodegradable.
-------------------------------	-----------------------

2-Ethylhexanol (104-76-7)

Persistence and degradability	Readily biodegradable.
Biodegradation	> 95 % @5d

12.3. Bioaccumulative potential

Solvent Naphta (Petroleum), Heavy Aromatic (64742-94-5)

Bioconcentration factor (BCF REACH)	< 100
Log Pow	3,8 – 4,8

2-Ethylhexanol (104-76-7)

Bioconcentration factor (BCF REACH)	25,33
Log Kow	2,9

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Hand over to officially registered waste disposal company. Recycle the material as far as possible. Waste suitable for incineration.
Waste materials	: Dispose of contents/container in accordance with licensed collector's sorting instructions and in accordance to local and regional legislation.
European List of Waste (LoW) code	: 13 07 03* - other fuels (including mixtures)

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG
14.1. UN number	
Not applicable	Not applicable
14.2. UN proper shipping name	
Not applicable	Not applicable
14.3. Transport hazard class(es)	
Not applicable	Not applicable
14.4. Packing group	
Not applicable	Not applicable
14.5. Environmental hazards	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	
14.6. Special precautions for user	
Overland transport No data available	
Transport by sea No data available	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Complete Petrol System Treatment ; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics. ; Solvent Naphta (Petroleum), Heavy Aromatic ; 2-Ethylhexanol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Complete Petrol System Treatment ; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics. ; Solvent Naphta (Petroleum), Heavy Aromatic ; 2-Ethylhexanol
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Complete Petrol System Treatment ; Solvent Naphta (Petroleum), Heavy Aromatic

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 5,38 % EU, 1993/13/EC; USA EPA Method 24/24A

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

Complete Petrol System Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.