



05000C2 Motor Oil 5W-30 Premium Synthetic C2 Citroën / Peugeot

Document version: Apr 22, 2024



Description

This premium synthetic fuel-saving 'MID SAPS' (ACEA C2) motor oil with PSA B71 2290 specification has been specially developed for Citroën and Peugeot cars and light commercial vehicles. This motor oil is also suitable for vehicles where SAE 5W-30 with ACEA C2 is specified. This motor oil meets the requirements of Euro 4 and Euro 5 engines with particulate filters (DPF).

According to the specifications of

ACEA C2
API CF / SN
Fiat 9.55535-S1
PSA B71 2290 <2017
Renault RN 0700

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001C2	1 L	6	450
05005C2	5 L	4	112
05020C2	20 L	1	-
05B20C2	20 L	1	-
05060C2	60 L	1	-
05205C2	205 L	1	-
05999C2	1000 L	1	-
P05000C2	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.856	kg/l	
Viscosity	5W-30		
Kinematic Viscosity at 40°C	57	mm ² /s	
Kinematic Viscosity at 100°C	10.1	mm ² /s	
Viscosity Index	170		
Dynamic Viscosity at -30°C	4700	mPa.s	
Flashpoint COC	214	°C	
Pourpoint	-39	°C	
Total Base Number	7.9	mgKOH/g	
Sulphated Ash	0.8	mass%	
High Temperature High Share	3	mPa.s	
Noack Evaporation Loss	10.9	mass%	

These characteristics are typical of current production. Variations in these characteristics may occur.