



52000S 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

Document version: 27 Apr 2024



Description

MPM 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic super twin motorcycle oil has been specially developed for the lubrication of 4-stroke motorcycles so slipping, sticking and stiff gear changes of the clutch are a thing of the past. This engine oil can also be used in primary chain cases and transmissions where an SAE 20W-50 is required.

According to the specifications of

API SL
JASO MA / MA2

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
52001S	1 L	6	450
52020S	20 L	1	30
52060S	60 L	1	6
52205S	205 L	1	2
52999S	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.849	kg/l
Viscosity	20W-50	
Kinematic Viscosity at 40°C	140	mm ² /s
Kinematic Viscosity at 100°C	20.70	mm ² /s
Viscosity Index	173	
Dynamic Viscosity at -15°C	1670	mPa.s
Flashpoint COC	218	°C
Pourpoint	-45	°C
Total Base Number	7.7	mgKOH/g
Sulphated Ash	0.94	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.