



20000 Brake Fluid DOT 4

Document version: Apr 27, 2024



Description

This DOT 4 brake fluid has been specially developed for use in all hydraulically operated brake and clutch systems fitted with drum or disk brakes and for which constructors specify a DOT 4 type brake fluid.

According to the specifications of

FMVSS 116 DOT 4
ISO 4925 (CLASS 4)
SAE J 1704

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 20250 | 0.25 L | 12 | - |
| 20000 | 0.5 L | 12 | - |
| 20001 | 1 L | 6 | - |
| 20004 | 4 L | 4 | 112 |
| 20005 | 5 L | 4 | 112 |
| 20020 | 20 L | 1 | 30 |
| 20060 | 60 L | 1 | 6 |
| 20205 | 205 L | 1 | 2 |
| 20999 | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|--------|--------------------|
| Density at 20°C | 1.05 | kg/l |
| Colour | yellow | |
| pH | 8 | |
| Kinematic Viscosity at 100°C | 2.3 | mm ² /s |
| Kinematic Viscosity at -40°C | 1200 | mm ² /s |
| Wet Boiling Point | 168 | °C |
| Boiling Point | 263 | °C |

These characteristics are typical of current production. Variations in these characteristics may occur.