



# 50000 PSF Power Steering Fluid SHVI Synthetic

Document version: Apr 27, 2024



## Description

This synthetic SHVI power steering fluid has been specially developed for use in power steering, shock absorbers, hydropneumatic suspensions, stability and traction systems, electric hydraulic convertible roof systems and central locking.

## According to the specifications of

BMW 81 22 9 407 758  
DIN 51524 T3  
Fiat 9.55550-AG3  
Ford WSS-M2C204-A  
ISO 7308  
MAN M 3289  
Opel/GM 1940 715 / 1940 766  
PSA S71 2710  
VW G 002 000 / 004 000  
VW TL 52 146  
Volvo 1161529

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
50001	1 L	6	450
50020	20 L	1	30
50060	60 L	1	6
50205	205 L	1	2
50999	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.83	kg/l	
Colour	green		
Kinematic Viscosity at 40°C	18.5	mm <sup>2</sup> /s	
Kinematic Viscosity at 100°C	6.3	mm <sup>2</sup> /s	
Viscosity Index	334		
Flashpoint COC	160	°C	
Pourpoint	-60	°C	
Brookfield Viscosity at -40°C	1150	mPa.s	

These characteristics are typical of current production. Variations in these characteristics may occur.