



06000S Motor Oil 0W-40 High Performance Street

Document version: 27 Apr 2024



Description

This premium synthetic high-grade motor oil has been specially developed for the latest generation of high performance engine performance. This motor oil ensures excellent protection against wear at high revolutions due to a superior lubrication film.

According to the specifications of

ACEA A3/B4
API SN
BMW LL-01
ILSAC GF-4
MB-Approval 229.5
Porsche A40
Renault RN 0700 / RN 0710
VW 502.00 / 505.00

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 06001S | 1 L | 6 | 450 |
| 06005S | 5 L | 4 | 112 |
| 06020S | 20 L | 1 | 30 |
| 06060S | 60 L | 1 | 6 |
| 06205S | 205 L | 1 | 2 |
| 06999S | 1000 L | 1 | - |
| P06000S | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|-------|--------------------|------------|
| Density at 15°C | 0.844 | kg/l | ASTM D4052 |
| Viscosity | 0W-40 | | |
| Kinematic Viscosity at 40°C | 80.1 | mm ² /s | ASTM D445 |
| Kinematic Viscosity at 100°C | 13.8 | mm ² /s | ASTM D445 |
| Viscosity Index | 178 | | ASTM D2270 |
| Dynamic Viscosity at -35°C | 6040 | mPa.s | ASTM D5293 |
| Flashpoint COC | 220 | °C | ASTM D92 |
| Pourpoint | -57 | °C | ASTM D6892 |
| Total Base Number | 10.1 | mgKOH/g | ASTM D2896 |
| Sulphated Ash | 1.09 | mass% | ASTM D874 |

These characteristics are typical of current production. Variations in these characteristics may occur.