



32000PN Pneumatic Oil 32

Document version: 27 Apr 2024



Description

This pneumatic oil 32 is a specific lubricant to lubricate pneumatic tools. The special additives in this oil obtains a good protection against corrosion of ferro an non-ferro metals. This oil has good protection against deposit in the pneumatic system, compatible with seals and gaskets made of synthetic material and excellent micro-fog properties. MPM Pneumatic Oil 32 can be used in air piping systems or micro-fog systems of hammers, pile divers and drilling equipment and pumps.

According to the specifications of

ISO 6743-11P

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
32001PN	1 L	6	450
32020PN	20 L	1	30
32060PN	60 L	1	6
32205PN	205 L	1	2
32999PN	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.873	kg/l
Viscosity	ISO VG 32	
Kinematic Viscosity at 40°C	33.3	mm ² /s
Kinematic Viscosity at 100°C	5.9	mm ² /s
Viscosity Index	122	
Flashpoint COC	198	°C
Pourpoint	-33	°C

These characteristics are typical of current production. Variations in these characteristics may occur.