



# 37000S UTTO GL-4 Premium Synthetic

Document version: May 11, 2024



## Description

This premium synthetic UTTO (Universal Tractor Transmission Oil) has been specially developed to provide improved lubricating properties, under various operating conditions, for wet brakes to prevent braking noise and in hydraulic systems. This oil is extremely suitable for applications where Volvo's specification level 97304 (WB 102)" is prescribed. However, it can also be used in torque converters for tractors, lift trucks and various off-road machines for which viscosity grade 75W-80 is recommended.

## Application manual

## According to the specifications of

AGCO ALLIS 821 XL  
 API GL-4  
 CASE IH MS 1206 / MS 1207 / MS 1209  
 CASE New Holland MAT 3505 / 3525 / 3540  
 DIN 51524 T3 HVLPD  
 Ford New Holland ESN-M2C134 D / FNHA-2-C-201.00  
 John Deere J20D  
 Kubota SUPER UDT<sup>2</sup> / UDT  
 Massey Ferguson M-1143 / M-1145  
 New Holland 410B / 410C  
 Valtra G2-08 / G2-B210  
 Volvo 97303/WB101 / 97304/WB102  
 ZF TE-ML 03E / 05F / 06K / 06R / 17E / 21F

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
37001S	1 L	6	450
37020S	20 L	1	30
37060S	60 L	1	6
37205S	205 L	1	2
37999S	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density	0.840	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	40.8	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	7.7	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	161		ASTM D2270
Dynamic Viscosity at -40°C	23700	mPa.s	ASTM D2983
Flashpoint COC	180	°C	ASTM D92
Pourpoint	-48	°C	ASTM D7346
Total Base Number	7.4	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.