



65000C PTFE Grease EP-2

Document version: 27 Apr 2024

Description

This marine PTFE grease EP-2 is a water-repellent teflon grease developed for application in shipping, metal and paper industries. This grease can be used as a lubricant for sliding surfaces, guide rails, cables, wire ropes, winches, pulleys and knee-joints. It is also ideal grease in the agricultural mechanization, passenger car and commercial vehicle sector. This Teflon PTFE white grease can be used in various types of bearings such as ball bearings, plain bearings and roller bearings.

According to the specifications of

DIN 51502
ISO 6743 / L-XCG HA2
KFK2U-35

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 65018C | 18 kg | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|-----------------------------|--------------|--------------------|
| Colour | white_yellow | |
| NLGI Classification | 2 | |
| Base Oil | mineral | |
| Additive | PTFE | |
| Kinematic Viscosity at 40°C | 100 | mm ² /s |
| Temperature Range | -20 / 120 | °C |
| Soap Thickener | Lithium | |

These characteristics are typical of current production. Variations in these characteristics may occur.