



BL059000 Marine Steering Oil

Document version: 27 Apr 2024



Description

This marine steering oil is a paraffinic oil with a high viscosity index for optimum operation of hydraulic systems with a high varying temperature range. This steering oil provides excellent protection against wear and corrosion, has a good filtration ability and fast de-aeration time resulting in less chance of foaming. It is fully compatible with seal materials such as nitrile, silicone and fluoropolymers (Teflon). MPM Marine Steering Oil is suitable for use in marine hydraulic steering systems including launch boats with Vetus hydrolysis.

According to the specifications of

DIN 51524 part 3
ISO 6743-4 Class HV 22

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL059001	1 L	6	450
BL059020	20 L	1	30
BL059060	60 L	1	6
BL059205	205 L	1	2
BL059999	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.859	kg/l
Kinematic Viscosity at 40°C	21.6	mm ² /s
Kinematic Viscosity at 100°C	5	mm ² /s
Viscosity Index	168	
Flashpoint COC	186	°C
Pourpoint	-39	°C

These characteristics are typical of current production. Variations in these characteristics may occur.